

# SWAS-AWBK 调节垫圈(黑色不锈钢)




耐药品 防反射 SUS 不锈钢

SWAS-AWBK



SWAS-AW



\*D=16以下: C0.2以下  
D=20以上: C0.5以下

## ● 型号指定

### SWAS-5-10-3-AWBK

产品符号 1 2 3 产品符号

3 t尺寸请从表中标有●的尺寸中选择。

- 外径和厚度的规格比一般的平垫圈更丰富。
- 用于确保长孔部位的座面以及与铝、树脂等临界座面压力低下的材料连接。
- 用于调节安装时的累积误差。

## ● 用途

高度调整 / 防止座面凹陷

## ● 材质、表面处理



	SWAS-AWBK
主体	SUS304 黑色不锈钢

单位: mm

型号	d 1	D 2	t 3					质量 (g)
			1	1.5	2	3	5	
SWAS-3-8-AWBK	3	8	●		●			0.35 - 0.69
SWAS-4-8-AWBK	4	8	●	●	●			0.3 - 0.6
SWAS-4-10-AWBK	4	10	●		●	●		0.53 - 1.6
SWAS-4-12-AWBK	4	12	●		●	●		0.8 - 2.4
SWAS-5-8-AWBK	5	8	●	●	●			0.25 - 0.49
SWAS-5-10-AWBK	5	10	●		●	●		0.47 - 1.4
SWAS-5-12-AWBK	5	12	●		●	●		0.74 - 2.2
SWAS-5-16-AWBK	5	16			●	●		2.9 - 4.3
SWAS-5-20-AWBK	5	20	●		●			2.3 - 4.7
SWAS-6-10-AWBK	6	10	●		●	●		0.4 - 1.2
SWAS-6-12-AWBK	6	12	●		●	●		0.68 - 2
SWAS-6-16-AWBK	6	16			●	●	●	2.7 - 6.8
SWAS-6-20-AWBK	6	20	●		●	●	●	2.3 - 11
SWAS-6-25-AWBK	6	25			●	●	●	7.3 - 18
SWAS-8-12-AWBK	8	12			●	●	●	1 - 2.5
SWAS-8-16-AWBK	8	16			●	●	●	2.4 - 6
SWAS-8-20-AWBK	8	20			●	●	●	4.2 - 10
SWAS-8-25-AWBK	8	25			●	●	●	7 - 17
SWAS-10-12-AWBK	10	12			●	●	●	0.55 - 1.4
SWAS-10-16-AWBK	10	16				●	●	2.9 - 4.8
SWAS-10-20-AWBK	10	20			●	●	●	3.7 - 9.3
SWAS-10-25-AWBK	10	25				●	●	9.8 - 16
SWAS-12-16-AWBK	12	16				●	●	2.1 - 3.5
SWAS-12-20-AWBK	12	20			●	●	●	3.2 - 8
SWAS-12-25-AWBK	12	25				●	●	9 - 15
SWAS-16-25-AWBK	16	25				●	●	6.9 - 11

1 散装零售 → P.xxxx

无尘洗净·无尘包装 → P.xxxx

螺纹切割 → P.xxxx

防松动 → P.xxxx

防脱落加工 → P.xxxx

本产品每包 1 个

可对应, 费用另计

不可对应

不可对应

不可对应