

- 带塑料垫的调平调节器。
- 螺纹采用不锈钢制。耐腐蚀性优良。
- 带橡胶膜片。
- 垫最大可倾斜15°。适用于倾斜面。

● 材质、表面处理



	FCMS-G
螺丝	SUS303
垫	玻璃纤维增强尼龙6 (亚光黑)
锁定螺母	SUS304
橡胶膜片	NBR (亚光黑) 肖氏硬度 A70



尺寸

单位: mm


型号 ¹	D	M (粗牙)		H	h	sw1	sw2	L1	静态容许载荷*1 (N)	质量 (g)
		螺纹公称直径	螺距							
FCMS-25-M6-G	25	M6	1	18.5	4	12	10	5.2	1000	27 - 31
FCMS-25-M8-G	25	M8	1.25	18.5	4	12	13	6.8	1000	36 - 44
FCMS-25-M10-G	25	M10	1.5	18.5	4	12	16	8.4	1000	51 - 61
FCMS-32-M8-G	32	M8	1.25	22.5	5	12	13	6.8	2000	39 - 48
FCMS-32-M10-G	32	M10	1.5	22.5	5	15	16	8.4	2000	68 - 84
FCMS-32-M12-G	32	M12	1.75	22.5	5	15	18	10.8	2000	91 - 114
FCMS-40-M8-G	40	M8	1.25	25.5	6	15	13	6.8	3000	56 - 70
FCMS-40-M10-G	40	M10	1.5	25.5	6	15	16	8.4	3000	76 - 87
FCMS-40-M12-G	40	M12	1.75	25.5	6	17	18	10.8	3000	110 - 140
FCMS-50-M8-G	50	M8	1.25	27.5	7	15	13	6.8	4000	70 - 85
FCMS-50-M10-G	50	M10	1.5	27.5	7	15	16	8.4	4000	86 - 100
FCMS-50-M12-G	50	M12	1.75	27.5	7	17	18	10.8	4000	122 - 148
FCMS-50-M16-G	50	M16	2	27.5	7	17	24	14.8	4000	178 - 230
FCMS-60-M10-G	60	M10	1.5	35.5	8.5	17	16	8.4	6000	98 - 120
FCMS-60-M12-G	60	M12	1.75	35.5	8.5	17	18	10.8	6000	137 - 165
FCMS-60-M16-G	60	M16	2	35.5	8.5	24	24	14.8	6000	262 - 316
FCMS-60-M20-G	60	M20	2.5	35.5	8.5	24	30	18	6000	386 - 505
FCMS-60-M24-G	60	M24	3	35.5	8.5	24	36	21.5	6000	523 - 695

*1: 表中数值为螺丝垂直于垫的状态下的值。在螺丝带角度的状态下, 会发生弯曲和屈曲应力, 导致静态容许载荷变小。
表中数值非保证值, 仅供参考。

型号	Lm (mm) ²									
	40	50	63	80	98	100	125	138	158	
FCMS-25-M6-G	●	●	●							
FCMS-25-M8-G	●	●	●							
FCMS-25-M10-G		●	●	●						
FCMS-32-M8-G	●	●	●							
FCMS-32-M10-G		●	●	●						
FCMS-32-M12-G			●	●		●				
FCMS-40-M8-G		●	●	●						
FCMS-40-M10-G		●	●	●						
FCMS-40-M12-G			●	●		●				
FCMS-50-M8-G		●	●	●						
FCMS-50-M10-G		●	●	●						
FCMS-50-M12-G			●	●		●				
FCMS-50-M16-G			●	●		●				
FCMS-60-M10-G		●	●	●						
FCMS-60-M12-G			●	●		●				
FCMS-60-M16-G				●		●	●			
FCMS-60-M20-G					●			●	●	
FCMS-60-M24-G					●			●	●	

- 型号指定

FCMS-25-M8-40-G



² 螺纹长度Lm请从表中标有●的尺寸中选择。

无尘洗净·无尘包装 → P.xxxx	螺纹切割 → P.xxxx	防松动 → P.xxxx	激光刻印 → P.xxxx
不可对应	欢迎洽询	不可对应	欢迎洽询