



## ● 材质、表面处理



|          | NSCSS-MP2     |
|----------|---------------|
| 主体       | S45C<br>无电解镀镍 |
| 内六角圆柱头螺栓 | SUSXM7        |

- 带固定孔的固定轴环。可使用固定孔，安装至轮、法兰、板等所有机械和装置上。
- 分离型。可完全分离轴孔部，因此便于安装和拆卸，不会损伤轴。
- 最适用于拆卸困难的机械和装置。

单位：mm

| 型号              | d  | B  | D  | F   | S*1 | P    | M(粗牙)*2 | 质量(g) |
|-----------------|----|----|----|-----|-----|------|---------|-------|
| NSCSS-8-8-MP2   | 8  | 8  | 25 | 8   | 4.5 | 16.5 | M3      | 22    |
| NSCSS-8-10-MP2  | 8  | 10 | 25 | 8   | 4.5 | 18   | M4      | 28    |
| NSCSS-8-12-MP2  | 8  | 12 | 28 | 8.5 | 5.5 | 18   | M5      | 43    |
| NSCSS-8-15-MP2  | 8  | 15 | 30 | 9   | 4.5 | 19   | M6      | 61    |
| NSCSS-10-10-MP2 | 10 | 10 | 30 | 9   | 5.5 | 20   | M4      | 38    |
| NSCSS-10-12-MP2 | 10 | 12 | 30 | 9   | 5.5 | 20   | M5      | 47    |
| NSCSS-10-15-MP2 | 10 | 15 | 35 | 10  | 5.5 | 22.5 | M6      | 82    |
| NSCSS-12-10-MP2 | 12 | 10 | 30 | 10  | 5.5 | 21   | M4      | 37    |
| NSCSS-12-12-MP2 | 12 | 12 | 30 | 10  | 5.5 | 21   | M5      | 45    |
| NSCSS-12-15-MP2 | 12 | 15 | 35 | 11  | 5.5 | 23.5 | M6      | 80    |
| NSCSS-15-10-MP2 | 15 | 10 | 32 | 11  | 5.5 | 24.5 | M4      | 40    |
| NSCSS-15-12-MP2 | 15 | 12 | 35 | 12  | 5.5 | 25   | M5      | 61    |
| NSCSS-15-15-MP2 | 15 | 15 | 40 | 13  | 5.5 | 27.5 | M6      | 106   |
| NSCSS-16-10-MP2 | 16 | 10 | 35 | 12  | 5.5 | 25.5 | M4      | 48    |
| NSCSS-16-12-MP2 | 16 | 12 | 35 | 12  | 5.5 | 25.5 | M5      | 59    |
| NSCSS-16-15-MP2 | 16 | 15 | 40 | 13  | 5.5 | 28   | M6      | 104   |
| NSCSS-20-10-MP2 | 20 | 10 | 40 | 14  | 5.5 | 30   | M4      | 62    |
| NSCSS-20-12-MP2 | 20 | 12 | 40 | 14  | 5.5 | 30   | M5      | 75    |
| NSCSS-20-15-MP2 | 20 | 15 | 45 | 15  | 5.5 | 32.5 | M6      | 125   |
| NSCSS-25-12-MP2 | 25 | 12 | 45 | 17  | 6.6 | 35   | M5      | 87    |
| NSCSS-25-15-MP2 | 25 | 15 | 50 | 18  | 6.6 | 37.5 | M6      | 150   |
| NSCSS-30-15-MP2 | 30 | 15 | 55 | 20  | 6.6 | 42.5 | M6      | 167   |
| NSCSS-35-15-MP2 | 35 | 15 | 60 | 23  | 6.6 | 47.5 | M6      | 192   |
| NSCSS-40-18-MP2 | 40 | 18 | 70 | 26  | 9   | 55   | M8      | 316   |
| NSCSS-50-22-MP2 | 50 | 22 | 85 | 32  | 11  | 67.5 | M10     | 547   |

\* 1：不附带固定螺丝。请另行准备。

\* 2：附带紧固用内六角圆柱头螺栓。

## ● 型号指定

NSCSS-8-8-MP2



无尘洗净·无尘包装 → P.xxxx

不可对应

螺纹切割 → P.xxxx

不可对应

防松动 → P.xxxx

不可对应

激光刻印 → P.xxxx

可对应, 费用另计