



● 材质、表面处理



	NCS-SS-SN2
主体	SUS304
内六角圆柱头螺栓	SUSXM7

- 带固定孔(内螺纹)的固定轴环。可使用固定孔(内螺纹), 安装至轮、法兰、板等所有机械和装置上。
- 分离型。可完全分离轴孔部, 因此便于安装和拆卸, 不会损伤轴。
- 最适用于拆卸困难的机械和装置。

单位: mm

型号	d	B	D	F	P	M(粗牙)*1	M1(粗牙)*2		质量(g)
							螺纹公称直径	螺距	
NCS-SS-8-8-SN2	8	8	25	8	14	M3	M3	0.5	24
NCS-SS-8-10-SN2	8	10	25	8	18	M4	M4	0.7	29
NCS-SS-8-12-SN2	8	12	28	8.5	18	M5	M4	0.7	46
NCS-SS-8-15-SN2	8	15	30	9	18	M6	M4	0.7	63
NCS-SS-10-10-SN2	10	10	30	9	20	M4	M4	0.7	41
NCS-SS-10-12-SN2	10	12	30	9	20	M5	M4	0.7	50
NCS-SS-10-15-SN2	10	15	35	10	20	M6	M4	0.7	86
NCS-SS-12-10-SN2	12	10	30	10	22	M4	M4	0.7	39
NCS-SS-12-12-SN2	12	12	30	10	22	M5	M4	0.7	49
NCS-SS-12-15-SN2	12	15	35	11	22	M6	M4	0.7	84
NCS-SS-15-10-SN2	15	10	32	11	25	M4	M4	0.7	42
NCS-SS-15-12-SN2	15	12	35	12	25	M5	M4	0.7	65
NCS-SS-15-15-SN2	15	15	40	13	25	M6	M4	0.7	111
NCS-SS-16-10-SN2	16	10	35	12	28	M4	M4	0.7	51
NCS-SS-16-12-SN2	16	12	35	12	28	M5	M4	0.7	63
NCS-SS-16-15-SN2	16	15	40	13	28	M6	M4	0.7	108
NCS-SS-20-10-SN2	20	10	40	14	30	M4	M5	0.8	64
NCS-SS-20-12-SN2	20	12	40	14	30	M5	M5	0.8	76
NCS-SS-20-15-SN2	20	15	45	15	30	M6	M5	0.8	129
NCS-SS-25-12-SN2	25	12	45	17	35	M5	M5	0.8	91
NCS-SS-25-15-SN2	25	15	50	18	35	M6	M5	0.8	156
NCS-SS-30-15-SN2	30	15	55	20	42	M6	M6	1.0	171
NCS-SS-35-15-SN2	35	15	60	23	47	M6	M6	1.0	195
NCS-SS-40-18-SN2	40	18	70	26	56	M8	M8	1.25	324
NCS-SS-50-22-SN2	50	22	85	32	66	M10	M8	1.25	571

*1: 附带紧固用内六角圆柱头螺栓。

*2: 不附带固定螺丝。请另行准备。

● 型号指定

NCS-SS-8-8-SN2



无尘洗净·无尘包装 → P.xxxx

欢迎洽询

螺纹切割 → P.xxxx

不可对应

防松动 → P.xxxx

不可对应

激光刻印 → P.xxxx

可对应, 费用另计